



DOWNLOAD: <https://hytly.com/2litbq>

Download

USB1 or USB2 Option 3: First connect the camera to the PC, then connect the camera to the target device (mobile phone, tablet, laptop, etc.) and select the Fluke Connect Web interface on the target device. For the first time connection of the camera to the target device, the target device (mobile phone, tablet, laptop, etc.) is automatically connected to the camera. When the camera is connected to the target device, the Connect Wizard will open on the target device. Connect the camera to the target device: Press, wait for the camera to display a message asking to press to confirm the connection, then press. Select the Fluke Connect Web interface: Press and hold until the image of the Fluke Connect Web interface appears on the target device. The Fluke Connect Web interface can be viewed on many mobile phones, tablets, and laptops: Android: From the home screen, tap the menu button, then tap Settings; Tap Applications, tap the Search icon, then tap the Fluke Connect application; Tap the Back arrow on the top left, then tap the arrow on the right; iPhone: Tap on the Settings icon, tap on General, tap on Configure, tap on Fluke Connect, then tap Fluke Connect; iPad: Tap the Settings icon, tap on General, tap on Fluke Connect, then tap Fluke Connect. Laptop: Power on the laptop, then wait for the Welcome screen, and tap on Fluke Connect. See the Appendix A for information on connecting the camera to various mobile devices. **Note:** After the target device is connected to the camera, it is configured as a remote camera. To stop the camera from receiving commands and receiving data from the target device, press. Setting up the device to view images and video To view images and video, the target device must be connected to the camera and configured as a remote camera. For instructions on connecting the camera to the target device, refer to the Connecting the camera to the target device in Setting up the camera to view images and video. **Note:** Once the camera and target device are connected and the camera has been configured as a remote camera, the camera will never be able to receive any commands from the target device. **See also:** [Get help with Fluke Connect Desktop software] 82157476af

Related links:

[Estadística Para Negocios Y Economía 12 Edición Pdf 137](#)
[Red Giant All Suites \(x64\) Incl License Keys](#)
[Huong Dan Crack Vietmap Cho Android](#)